

SAFETY DATA SHEET

METHYL ETHYL KETONE

Page 1

Issued: 19/01/20

Revision No: 002

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: METHYL ETHYL KETONE

CAS number: 78-93-3

EINECS number: 201-159-0

Index number: 606-002-00-3 **Synonyms:** BUTANONE

Company name: 6 Science LTD

Unit 6

10 Great Northern Way

Netherfield Nottingham NG4 2HD

Emergency tel: 0044 (0) 115 779 0196

Email: info@6science.co.uk

2. HAZARDS IDENTIFICATION

Main hazards: Highly flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking.

Vapours may cause drowsiness and dizziness.

Other hazards: In use, may form flammable / explosive vapour-air mixture.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients: METHYL ETHYL KETONE 100.000%

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause

coughing or wheezing.

4. FIRST AID MEASURES (ACTION)

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a doctor.

Issued: 19/01/20

SAFETY DATA SHEET

METHYL ETHYL KETONE

Page 2

5. FIRE-FIGHTING MEASURES

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder. Use water spray to

cool containers.

Exposure hazards: Highly flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture. Vapour

may travel considerable distance to source of ignition and flash back.

Protection of fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin

and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by

an appropriate method. Do not use equipment in clean-up procedure which may produce

sparks.

7. HANDLING AND STORAGE

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do

not handle in a confined space. Avoid the formation or spread of mists in the air. Smoking is

forbidden. Use non-sparking tools.

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of

ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and

electrical equipment are not a source of ignition.

Suitable packaging: Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Workplace exposure limits

WEL (8 hr TWA): 600 mg/m3 **WEL (15 min STEL):** 899 mg/m3

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not

a source of ignition.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Protective gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Issued: 19/01/020

SAFETY DATA SHEET

METHYL ETHYL KETONE

Page 3

9. PHYSICAL AND CHEMICAL PROPERTIES

State: Liquid

Colourless

Odour: Characteristic odour

Solubility in water: Miscible

Also soluble in: Most organic solvents.

Boiling point/range°C: 79.6 **Melting point/range°C:** -85.9

Flash point°C: -7
Relative density: 0.805

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions. Stable at room temperature.

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

Materials to avoid: Strong oxidising agents. Strong acids.

Haz. decomp. products: In combustion emits toxic fumes.

11. TOXICOLOGICAL INFORMATION

Acute toxicity: METHYL ETHYL KETONE

IPR RAT LD50 607 mg/kg ORL MUS LD50 4050 mg/kg ORL RAT LD50 2737 mg/kg

Routes of exposure: Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

Mobility: Readily absorbed into soil.

Persistence and degradability: Biodegradable.

Bioaccumulative potential: No bioaccumulation potential.

Other adverse effects: Negligible ecotoxicity.

13. DISPOSAL CONSIDERATIONS

NB: The user's attention is drawn to the possible existence of regional or national regulations

regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

UN no: 1193 **ADR Class:** 3

Packing group: II Classification code: F1

Shipping name: ETHYL METHYL KETONE (METHYL ETHYL KETONE)

Page 4

SAFETY DATA SHEET

METHYL ETHYL KETONE

Labelling: 3 Hazard ID no: 33



IMDG/IMO

UN no: 1193 Class: 3

Packing group: II EmS: 3-06

Marine pollutant: NO

Labelling: 3

IATA / ICAO

UN no: 1193 Class: 3

Packing group: II

Packing instructions: 305(P&CA); 307(PAO)

Labelling: 3

15. REGULATORY INFORMATION

Hazard symbols: Highly flammable.

Irritant.





Risk phrases: R11: Highly flammable.

R36: Irritating to eyes.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Safety phrases: S16: Keep away from sources of ignition - No smoking.

S25: Avoid contact with eyes.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical

advice.

S33: Take precautionary measures against static discharges.

S39: Wear eye / face protection.

Note: The regulatory information given above only indicates the principal regulations specifically

applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all

applicable national, international and local regulations or provisions.

SAFETY DATA SHEET

METHYL ETHYL KETONE

Page 5

16. OTHER INFORMATION

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall

be used only as a guide. This company shall not be held liable for any damage resulting from

handling or from contact with the above product.