

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Version 1
Print Date 12.08.2025**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifiers**

Product name : Dichloromethane

Product Number : DCM810
Brand : 6Science LTD
Index-No. : 602-004-00-3
REACH No. : 01-2119480404-41-XXXX
CAS-No. : 75-09-2

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, Manufacture of substances

1.3 Details of the supplier of the safety data sheet

Company : 6 Science LTD
Unit 2, Welby Grange Business Park
Melton Mowbary, Leicestershire, LE143EF
UNITED KINGDOM

Telephone : +44 (0)115 7790196
E-mail address : info@6science.co.uk

1.4 Emergency telephone

Emergency Phone # : +44 (0)870 8200418 (CHEMTREC)

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567**

Skin irritation, (Category 2)	H315: Causes skin irritation.
Eye irritation, (Category 2)	H319: Causes serious eye irritation.
Carcinogenicity, (Category 2)	H351: Suspected of causing cancer.
Specific target organ toxicity - single exposure, (Category 3), Central nervous system	H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008 as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567

Pictogram



Signal Word

Warning

Hazard Statements

H315

Causes skin irritation.

H319

Causes serious eye irritation.

H336

May cause drowsiness or dizziness.

H351

Suspected of causing cancer.

Precautionary Statements

P202

Do not handle until all safety precautions have been read and understood.

P261

Avoid breathing mist or vapors.

P264

Wash skin thoroughly after handling.

P302 + P352

IF ON SKIN: Wash with plenty of water.

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313

IF exposed or concerned: Get medical advice/ attention.

Supplemental Hazard Statements

none

Reduced Labeling (<= 125 ml)

Pictogram



Signal Word

Warning

Hazard Statements

H351

Suspected of causing cancer.

Precautionary Statements

P202

Do not handle until all safety precautions have been read and understood.

P308 + P313

IF exposed or concerned: Get medical advice/ attention.

Supplemental Hazard Statements

none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information:

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Methylene chloride
DCM

Formula : CH₂Cl₂
Molecular weight : 84.93 g/mol
CAS-No. : 75-09-2
EC-No. : 200-838-9
Index-No. : 602-004-00-3

Component		Classification	Concentration
Dichloromethane			
CAS-No.	75-09-2	Skin Irrit. 2; Eye Irrit. 2; Carc. 2; STOT SE 3; H315, H319, H351, H336 Concentration limits: 20 %: STOT SE 3, H336;	<= 100 %
EC-No.	200-838-9		
Index-No.	602-004-00-3		

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air. Call in physician.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water Foam Carbon dioxide (CO₂) Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Hydrogen chloride gas

Combustible.

Development of hazardous combustion gases or vapours possible in the event of fire.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Suppress (knock down) gases/vapors/mists with a water spray jet. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures**6.1 Personal precautions, protective equipment and emergency procedures**

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Evacuate the danger area, observe emergency procedures, consult an expert.

For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage**7.1 Precautions for safe handling****Advice on safe handling**

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities**Storage conditions**

Tightly closed. Keep in a well-ventilated place. Keep locked up or in an area accessible only to qualified or authorized persons.

Heat sensitive. Handle and store under inert gas.

Storage class

Storage class (TRGS 510): 6.1C: Combustible, acute toxic Cat.3 / toxic compounds or compounds which causing chronic effects

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Control parameters	Value	Basis
Dichloromethane	75-09-2	TWA	100 ppm 353 mg/m ³	UK. EH40 WEL - Workplace Exposure Limits
	Remarks	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		TWA	100 ppm 353 mg/m ³	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
		Identifies the possibility of significant uptake through the skin Indicative		
		STEL	200 ppm 706 mg/m ³	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
		Identifies the possibility of significant uptake through the skin Indicative		
		STEL	200 ppm 706 mg/m ³	UK. EH40 WEL - Workplace Exposure Limits
		Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		

Biological occupational exposure limits

Component	CAS-No.	Parameters	Value	Biological specimen	Basis
Dichloromethane	75-09-2	Carbon monoxide	30parts per million	End-tidal breath	UK. Biological monitoring guidance values
	Remarks	After shift			

Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Inhalation	Acute systemic effects	706 mg/m ³
Workers	Inhalation	Long-term systemic effects	353 mg/m ³
Workers	Skin contact	Long-term systemic effects	4750mg/kg BW/d
Consumers	Ingestion	Long-term systemic effects	0.06mg/kg BW/d
Consumers	Inhalation	Long-term systemic effects	88.3 mg/m ³

Consumers	Skin contact	Long-term systemic effects	2395mg/kg BW/d
Consumers	Inhalation	Acute systemic effects	353 mg/m3

Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	0.583 mg/kg
Sea water	0.194 mg/l
Fresh water	0.54 mg/l
Sea sediment	1.61 mg/kg
Fresh water sediment	4.47 mg/kg
Onsite sewage treatment plant	26 mg/l
Aquatic intermittent release	0.27 mg/l

8.2 Exposure controls

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 120 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

Body Protection

protective clothing

Respiratory protection

Recommended Filter type: Filter AX (EN 371)

The entrepreneur has to ensure that maintenance, cleaning and testing of respiratory protective devices are carried out according to the instructions of the producer. These measures have to be properly documented.

Control of environmental exposure

Do not let product enter drains.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- a) Physical state liquid
- b) Color colorless
- c) Odor ether-like
- d) Melting Melting point/ range: -97 °C
point/freezing point
- e) Initial boiling point 39.8 - 40 °C

and boiling range

- | | |
|---|--|
| f) Flammability (solid, gas) | No data available |
| g) Upper/lower flammability or explosive limits | Upper explosion limit: 22 %(V)
Lower explosion limit: 13 %(V) |
| h) Flash point | does not flash |
| i) Autoignition temperature | 605 °C
at 1,013 hPa - DIN 51794 |
| j) Decomposition temperature | No data available |
| k) pH | No data available |
| l) Viscosity | Viscosity, kinematic: No data available
Viscosity, dynamic: 0.42 mPa.s at 25 °C |
| m) Water solubility | 13.2 g/l at 25 °C |
| n) Partition coefficient: n-octanol/water | log Pow: 1.25 at 20 °C - Bioaccumulation is not expected. |
| o) Vapor pressure | 584 hPa at 25 °C |
| p) Density | 1.325 g/mL at 25 °C |
| Relative density | No data available |
| q) Relative vapor density | No data available |
| r) Particle characteristics | No data available |
| | |
| s) Explosive properties | Not classified as explosive. |
| t) Oxidizing properties | none |

9.2 Other safety information

Relative vapor density	2.93
------------------------	------

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Sensitivity to light

The product is chemically stable under standard ambient conditions (room temperature) .

Contains the following stabilizer(s):

2-methyl-2-butene (>0.005 - <0.015 %)

10.3 Possibility of hazardous reactions

Risk of explosion with:

Alkali metals

nitrogen oxides

nitrogen dioxide

Potassium

sodium azide
perchloric acid
Nitric acid
aluminium chloride
Amines
Oxygen
(as liquefied gas)
powdered aluminium
sodium
aromatic hydrocarbons
with
powdered aluminium
Exothermic reaction with:
Alkaline earth metals
Powdered metals
amides
alcoholates
nonmetallic oxides
potassium tert-butanolate
sodium amide
Lithium

10.4 Conditions to avoid

no information available

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - male and female - > 2,000 mg/kg

(OECD Test Guideline 401)

LC50 Inhalation - Mouse - 4 h - 86 mg/l - vapor

Remarks: (ECHA)

Symptoms: Possible damages:, mucosal irritations

LD50 Dermal - Rat - male and female - > 2,000 mg/kg

(OECD Test Guideline 402)

Skin corrosion/irritation

Skin - Rabbit

Result: Irritations - 4 h

(OECD Test Guideline 404)

Remarks: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: Eye irritation

Remarks: (ECHA)

Remarks: Risk of corneal clouding.

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: negative

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Mutagenicity (mammal cell test): chromosome aberration.

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: positive

Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: positive

Test Type: In vivo micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Gavage

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Suspected of causing cancer.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause drowsiness or dizziness. - Central nervous system

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information**Endocrine disrupting properties****Product:**

Assessment

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Repeated dose toxicity - Rat - male and female - Oral - 104 Weeks - NOAEL (No observed adverse effect level) - 6 mg/kg

Repeated dose toxicity - Rat - male and female - Inhalation - 104 Weeks

RTECS: PA8050000

Dizziness, Nausea, Vomiting, narcosis, Cough, irritant effects, Unconsciousness, Shortness of breath, respiratory paralysis, somnolence, depressed respiration, CNS disorders, inebriation

Risk of corneal clouding.

The following applies to aliphatic halogenated hydrocarbons in general: systemic effect: narcosis, cardiovascular disorders. Toxic effect on liver, kidneys.
Dichloromethane is metabolized in the body producing carbon monoxide which increases and sustains carboxyhemoglobin levels in the blood, reducing the oxygen-carrying capacity of the blood.
To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects:

After absorption of large quantities:

CNS disorders
Drowsiness
Dizziness
drop in blood pressure
Cardiac irregularities
depressed respiration
inebriation
Unconsciousness
narcosis

Swallowing may result in damage to the following:

Liver
Kidney

The following applies to aliphatic halogenated hydrocarbons in general: systemic effect: narcosis, cardiovascular disorders. Toxic effect on liver, kidneys.

Other dangerous properties can not be excluded.

This substance should be handled with particular care.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Pimephales promelas (fathead minnow) - 193.00 mg/l - 96 h Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates	static test LC50 - Daphnia magna (Water flea) - 27 mg/l - 48 h (US-EPA)
Toxicity to bacteria	static test EC50 - activated sludge - 2,590 mg/l - 40 min (OECD Test Guideline 209)
Toxicity to fish(Chronic toxicity)	flow-through test LC50 - Pimephales promelas (fathead minnow) - 471 mg/l - 8 d Remarks: (ECHA)

12.2 Persistence and degradability

Biodegradability aerobic - Exposure time 28 d

Result: 68 % - Readily biodegradable.
(OECD Test Guideline 301D)

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 6 Weeks
- 250 µg/l(Dichloromethane)

Bioconcentration factor (BCF): 2 - 5.4
(OECD Test Guideline 305)

Cyprinus carpio (Carp) - 6 Weeks
- 25 µg/l(Dichloromethane)

Bioconcentration factor (BCF): 6 - 40
(OECD Test Guideline 305)

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment	: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.
------------	---

12.7 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. Notice Directive on waste 2008/98/EC.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1593

IMDG: 1593

IATA: 1593

14.2 UN proper shipping name

ADR/RID: DICHLOROMETHANE

IMDG: DICHLOROMETHANE

IATA: Dichloromethane

14.3 Transport hazard class(es)

ADR/RID: 6.1

IMDG: 6.1

IATA: 6.1

14.4 Packaging group

ADR/RID: III

IMDG: III

IATA: III

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

Tunnel restriction code : (E)

Further information : No data available

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006.

Authorisations and/or restrictions on use

REACH - Restrictions on the manufacture, : Dichloromethane
placing on the market and use of certain
dangerous substances, mixtures and articles
(Annex XVII)

Regulation (EU) No 2024/590 on substances that : Dichloromethane
deplete the ozone layer

Other regulations

Observe work restrictions regarding maternity protection in accordance to Dir 92/85/EEC or stricter national regulations where applicable.

Take note of Dir 94/33/EC on the protection of young people at work.

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has been carried out for this substance.

SECTION 16: Other information

Full text of H-Statements

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. 6Science LTD shall not be held liable for any damage resulting from handling or from contact with the above product.

Annex: Exposure scenario

Identified uses:

Use: Industrial use resulting in manufacture of another substance (use of intermediates)

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
PC19: Intermediate
PROC1: Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
ERC1: Manufacture of substances

Use: Formulation of preparations

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 10: Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)
PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
PROC9: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
ERC2: Formulation of preparations

Use: Industrial use of processing aids in processes and products, not becoming part of articles

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
PC20: Products such as pH-regulators, flocculants, precipitants, neutralization agents
PC21: Laboratory chemicals
PROC1: Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

Use: Used as laboratory reagent.

SU 22: Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
SU 3, SU 22, SU24: Industrial uses: Uses of substances as such or in preparations at industrial sites, Professional uses: Public domain (administration, education, entertainment, services, craftsmen), Scientific research and development
PC21: Laboratory chemicals
PROC10: Roller application or brushing

PROC15: Use as laboratory reagent
ERC4, ERC8a: Industrial use of processing aids in processes and products, not becoming part of articles, Wide dispersive indoor use of processing aids in open systems

Use: Surface treatment

SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
SU 3, SU9: Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of fine chemicals
PC35: Washing and cleaning products (including solvent based products)
PC1: Adhesives, sealants
PROC5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/ or significant contact)
PROC7: Industrial spraying
PROC10: Roller application or brushing
PROC13: Treatment of articles by dipping and pouring
ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

1. Short title of Exposure Scenario: Industrial use resulting in manufacture of another substance (use of intermediates)

Main User Groups	: SU 3
Sectors of end-use	: SU 3, SU9
Chemical product category	: PC19
Process categories	: PROC1, PROC2, PROC3, PROC4
Environmental Release Categories	: ERC1:

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC1

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PC19

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use) : High volatile liquid

Frequency and duration of use

Application duration : > 4 h
Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source**Environment**

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC1	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.00343 mg/kg BW/d	0
PROC1	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	0.0248 mg/m ³	0
PROC2	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.137 mg/kg BW/d	0
PROC2	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	61.9 mg/m ³	0.175
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.0686 mg/kg BW/d	0
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	124 mg/m ³	0.351
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.686 mg/kg BW/d	0
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	248 mg/m ³	0.703

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Formulation of preparations

Main User Groups	: SU 3
Sectors of end-use	: SU 10
Process categories	: PROC3, PROC4, PROC5, PROC8b, PROC9
Environmental Release Categories	: ERC2:

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC2

Product characteristics

Concentration of the Substance in Mixture/Article	: Covers the percentage of the substance in the product up to 100 % (unless stated differently).
---	--

2.2 Contributing scenario controlling worker exposure for: PROC3, PROC4, PROC5, PROC8b, PROC9

Product characteristics

Concentration of the Substance in Mixture/Article	: Covers the percentage of the substance in the product up to 100 % (unless stated differently).
Physical Form (at time of use)	: High volatile liquid

Frequency and duration of use

Application duration	: > 4 h
Frequency of use	: 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor	: Indoor
------------------	----------

Technical conditions and measures

Use only in area provided with appropriate exhaust ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary

(REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	124 mg/m ³	0.351
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.0686 mg/kg BW/d	0
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.686 mg/kg BW/d	0
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	248 mg/m ³	0.703
PROC5	ECETOC TRA	With Local Exhaust Ventilation	Dermal	1.37 mg/kg BW/d	0
PROC5	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	88.5 mg/m ³	0.251
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	26.5 mg/m ³	0.075
PROC8b	ECETOC TRA	With Local Exhaust Ventilation	Dermal	1.37 mg/kg BW/d	0
PROC9	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	70.8 mg/m ³	0.201
PROC9	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.686 mg/kg BW/d	0

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Industrial use of processing aids in processes and products, not becoming part of articles

Main User Groups	: SU 3
Sectors of end-use	: SU 3, SU9
Chemical product category	: PC20, PC21
Process categories	: PROC1, PROC2, PROC3, PROC4

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC4

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4, PC20, PC21

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : High volatile liquid

Frequency and duration of use

Application duration : > 4 h

Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC1	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	0.0248 mg/m ³	0
PROC1	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.00343 mg/kg BW/d	0
PROC2	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	61.9 mg/m ³	0.175
PROC2	ECETOC TRA	Without Local	Dermal	0.137 mg/kg	0

		Exhaust Ventilation		BW/d	
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.0686 mg/kg BW/d	0
PROC3	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	124 mg/m ³	0.351
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Dermal	0.686 mg/kg BW/d	0
PROC4	ECETOC TRA	Without Local Exhaust Ventilation	Inhalation	248 mg/m ³	0.703

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Used as laboratory reagent.

Main User Groups : **SU 22**
 Sectors of end-use : **SU 3, SU 22, SU24**
 Chemical product category : **PC21**
 Process categories : **PROC10, PROC15**
 Environmental Release Categories : **ERC4, ERC8a:**

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC4, ERC8a

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC10, PROC15, PC21

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : High volatile liquid

Frequency and duration of use

Application duration : > 4 h
 Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure
Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC10	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	88.5 mg/m ³	0.251
PROC10	ECETOC TRA	With Local Exhaust Ventilation	Dermal	2.74 mg/kg BW/d	0.001
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Dermal	0.0343 mg/kg BW/d	0
PROC15	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	35.4 mg/m ³	0.1

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).

1. Short title of Exposure Scenario: Surface treatment

Main User Groups : **SU 3**
Sectors of end-use : **SU 3, SU9**
Chemical product category : **PC35, PC1**
Process categories : **PROC5, PROC7, PROC10, PROC13**
Environmental Release Categories : **ERC4:**

2. Exposure scenario

2.1 Contributing scenario controlling environmental exposure for: ERC4

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

2.2 Contributing scenario controlling worker exposure for: PROC5, PROC7, PROC10, PROC13, PC35, PC1

Product characteristics

Concentration of the Substance in Mixture/Article : Covers the percentage of the substance in the product up to 100 % (unless stated differently).

Physical Form (at time of use) : High volatile liquid

Frequency and duration of use

Application duration : > 4 h

Frequency of use : 220 days/year

Other operational conditions affecting workers exposure

Outdoor / Indoor : Indoor

Technical conditions and measures

Provide adequate ventilation., Good work practice required.

Organizational measures to prevent /limit releases, dispersion and exposure

Ensure operatives are trained to minimize exposures.

Conditions and measures related to personal protection, hygiene and health evaluation

Wear suitable gloves tested to EN374., For personal protection see section 8.

3. Exposure estimation and reference to its source

Environment

A chemical safety assessment was performed according REACH Article 14(3), Annex I, sections 3 (Environmental Hazard assessment) and 4 (PBT/vPvB Assessment). As no hazard was identified, an exposure assessment and risk characterisation is not necessary (REACH Annex I section 5.0).

Workers

Contributing Scenario	Exposure Assessment Method	Specific conditions	Value	Level of Exposure	RCR*
PROC5	ECETOC TRA	With Local Exhaust Ventilation	Dermal	1.37 mg/kg BW/d	0
PROC5	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	88.5 mg/m ³	0.251
PROC7	ECETOC TRA	With Local Exhaust Ventilation	Dermal	4.29 mg/kg BW/d	0.001
PROC7	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	88.5 mg/m ³	0.251
PROC10	ECETOC TRA	With Local Exhaust	Inhalation	88.5 mg/m ³	0.251

		Ventilation			
PROC10	ECETOC TRA	With Local Exhaust Ventilation	Dermal	2.74 mg/kg BW/d	0.001
PROC13	ECETOC TRA	With Local Exhaust Ventilation	Inhalation	88.5 mg/m ³	0.251
PROC13	ECETOC TRA	With Local Exhaust Ventilation	Dermal	1.37 mg/kg BW/d	0

*Risk characterisation ratio

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

Please refer to the following documents: ECHA Guidance on information requirements and chemical safety assessment Part D: Exposure Scenario Building, Part E: Risk Characterisation and Part G: Extending the SDS; VCI/Cefic REACH Practical Guides on Exposure Assessment and Communications in the Supply Chain; CEFIC Guidance Specific Environmental Release Categories (SPERCs).